



DANLIST
PRECISION CUTTING & DRILLING

MORSØ - UPA

Frame Assembling Machine

Automatic, pneumatic,
operated by dual hand release system

Bench Model

Ideal machine for frame assembling

- ▼ Dual hand operation for maximum operator safety
- ▼ Exact 45° assembling
- ▼ No noise

MORSØ-UPA is an automatic, pneumatic bench model which is operated by a dual hand release system as well as a pneumatic foot pedal for clamping the frames.

Therefore the Morsø-UPA is 100 % safe to operate. The **MORSØ-UPA** has built in extension arms for supporting long mouldings.



MORSØ - UPA

Frame Assembling Machine

Automatic - Pneumatic
TECHNICAL DATA

SUBJECT	SPECIFICATION
Air pressure	6 – 8 bar
Wedge sizes	5, 7, 10 and 12 mm
Thickness of moulding, min.	6 mm (¼")
Thickness of moulding, max.	65 mm (2 ½")
Width of moulding, min.	6 mm (¼")
Width of moulding, max.	150 mm (6")
Distance between wedges, max	130 mm (5")
Height, working bench	272 mm (11")
Machine dimension:	
Length x width x height	575 x 330 x 490 mm (22 x 13 x 19")
Weight	50 kilos (110 lbs)

The main features of the MORSØ UPA are:

- Bench model
- Operated by a dual hand release system ensuring maximum operator safety.
- Noiseless operation
- Exact 45° assembling
- Built to last

MORSØ UPA is delivered with: ACCESSORIES:

- Two adjustable stops for min. and max. wedge position.
- Single pressure pad for plain mouldings.
- Two double pressure pads for mouldings with different profiles.
- Frontal clamping device holding the corners tightly together to create a perfect joint.
- Adjustable fences for all angles, i.e. rectangular, hexagonal, and octagonal frames
- Built-in support arms for long mouldings.
- Two refillable solid-steel cartridges for 7 and 10 mm wedges, respectively.
- Air filter.
- Oil lubricator.
- One box of 7 mm wedges (5000 pcs).
- One box of 10 mm wedges (2700 pcs).
- 5 mm steel cartridge
- 12 mm steel cartridge
- 5 mm wedges – 1 box 5000 pcs
- 12 mm wedges – 1 box 5400 pcs
- Stand for the machine: Dimensions: Min. height: 735 mm (29") Max. height: 735 mm (29") Width: 560 mm (22") Length: 320 mm (13")
- Shelf: Width x length: 450 x 320 cm (18 x 13")


Double pressure pads:

One for mouldings with standard profile and one for mouldings with reversed profile.

Padded with synthetic fibres ensuring no marks at all are left on the frame.


Flat pressure pad for plain mouldings.

Padded with synthetic fibres ensuring no marks at all are left on the frame.


Solid steel cartridges:

5, 7, 10, and 12 mm.


MODELS

MORSØ - UPH

MORSØ - UPM

MORSØ - UPAKS

DISTRIBUTOR
